



## **Overview**

The EV5 apartment station enables an occupant to answer visitor calls from the communal entrance with a two-way simultaneous video conversation. The occupant can then open the door to the visitor directly from the apartment station.

Constructed from hard wearing HIPS plastic in a sleek and modern design. The HIPS plastic has a high impact resistance and toughness, is mark resistant and finished in matte white. They are a 'surface mount' design for easy installation.

The  $5^{\prime\prime}$  colour display has a resolution of 480 x 272 pixels and is equipped with On Screen Display (OSD). The end-user can easily adjust the image brightness, contrast and colour using the soft touch buttons.

- 5" color display with OSD
- Handset with magnetic hang-up
- Discreet LED Indicators
- 8 capacitive 'Soft-touch' buttons including door unlock, privacy, concierge call back, ring tone volume settings (low/medium/maximum) and controls for the OSD.
- 10 Selectable ringtones.
- Mute call tone when on privacy, with LED alert
- UX2 for auxiliary functions and call to the porter

205mm 44.5mm

## **ACCESSORIES**



**AGT K TV** 

Desktop stand. 10mm thick transparent plexiglass stand supplied with white RJ45 cable and metallic grey terminal board cover with PMMA laminate.







## **Technical characteristics**

MODEL EV5 (840CA-0070) **Buttons** 8 capacitive 'Soft-touch' buttons Privacy 6 timeout settings, 5mins, 30mins, 1hr, 4hrs, 8hrs or 12hrs. Can be disabled or latched on/off Call tone 10 Selectable ringtones. Muted call tone when on privacy. Operating Voltage 12-15V DC (13.8V Nominal) **Power Consumption** ~0.15W Idle, ~1.9W Active, 2.5W Max. Cabling CAT5/ CW1308 6 pair minimum (leaves 1x core spare) - Note: 4 pair can be used if Door Open LED function omitted Connections 10-way Screw Terminal - slotted head 205 x 190 x 27 (without receiver) 205 x 190 x 44.5mm (with receiver) (approximate excluding cable) Dimensions White Colour